

NEGATIVE LOAD TABLE

18" TITE-LOC PLUS, .032 ALUMINUM

Span	AISI Design Load, 2.0 Safety Factor	USOE Design Load: 1.65 Safety Factor
2.00	-52.20	-63.30
2.50	-47.00	-57.00
3.00	-41.80	-50.70
3.50	-36.60	-44.36
4.00	-31.40	-38.10
4.50	-26.20	-31.80
5.00	-21.00	-25.50

NOTES

1. Testing conducted per ASTM E-1592 Air Bag testing, negative uplifts.
2. Actual testing conducted at 2' 0 and 5' 0" spacing. Intermediate values have been interpolated.
3. All tests were performed by Farabaugh Engineering & Testing.
- 4 Tests results are highlighted.
5. Open Frame Testing, panel clips attached to 16 Gauge Z Purlins for test module above

PETERSEN ALUMINUM CORPORATION

PAC-CLAD.COM SALES@PETERSENMAIL.COM

HQ: 1005 Tonne Road
 Elk Grove Village, IL 60007
 P: 800-PAC-CLAD
 F: 800-722-7150

9060 Junction Drive
 Annapolis Junction, MD 20701
 P: 800-344-1400
 F: 301-953-7627

10551 PAC Road
 Tyler, TX 75707
 P: 800-441-8661
 F: 903-581-8592

102 Northpoint Parkway
 Acworth, GA 30102
 P: 800-272-4482
 F: 770-420-2533

1800 S. 7th Ave., Suite 130
 Phoenix, AZ 85007
 P: 833-750-1935
 F: 602-254-6504

1885 Station Parkway NW, Suite B
 Andover, MN 55304
 P: 877-571-2025
 F: 866-901-2935