



# Farabaugh Engineering and Testing Inc.

Project No. T265-21

Report Date: October 30, 2021

No. Pages: 18 pgs (Inclusive)

## PERFORMANCE REPORT


### ASTM E330 UNIFORM LOAD TEST

ON

MODULARAL METAL PANEL  
3" DEEP X 30" WIDE COVERAGE X 0.080" ALUMINUM

FOR

PETERSEN ALUMINUM CORP.  
10551 PAC RD.  
TYLER, TX. 75707



Prepared by:

Paul G. Farabaugh

Approved by:

Daniel G. Farabaugh

**DANIEL G. FARABAUGH, P.E.**  
255 Saunders Station Rd  
Trafford, PA 15085  
412-373-9238



AAMA  
ACCREDITED  
LABORATORY



FLORIDA  
ACCREDITED  
LABORATORY  
& QC ENTITY

## STRUCTURAL TESTING

### **Purpose**

The purpose of this test is to establish the structural loads on a 8'-0" wide x 8'-0" high wall system.

### **Test Completion Date**

10-28-21

### **Test Specimen**

Manufacturer: Petersen Aluminum Corp.  
10551 Pac Rd.  
Tyler, TX. 75707

Test Specimen: ModularAL Metal Panel, - 3" Deep x 30" wide coverage x 0.080" alum.  
(See Dwg A206 for actual dimension)

Mock-up Size: 96" wide X 96 high (nominal) consisting of 12 panels x 30" (or 18") wide x various lengths of 0.080" thick aluminum panels. All panels are 3" deep.  
See page 8 for panel layout

### **Mock up -Installation**

- The test setup consisted of a 96" wide x 96" high mock-up that used 6" x 16 ga. vertical channel studs spaced at 24" o.c that were attached to the top and bottom horizontal 16 ga. channel track.
- 5/8" thick Densglass Gypsum board was attached to the vertical stud supports using #6 x 1" lg. self -drilling fasteners spaced at 10" o.c.
- The panel support consisted of 16 ga. Zee horizontal supports attached thru the gypsum board and into 16 ga. vertical channel supports using #12 x 1-1/2" long wafer-head self -drilling screws. Additional vertical Zee supports were used at the panel clip locations.

- 1" foam board insulation was between all zee supports and entire mock-up was covered with Ice and Water Shield.
- A 16 ga. lower "J" channel was along the bottom and two sides of the mock-up. The "J" channel had predrilled holes thru the top leg and a #12 -14 x 1-1/2" long wafer-head self-drilling screws spaced at 22" o.c. secured the lower "J" channel thru the gypsum board and into the 16 ga. stud/channel track. The lower "J" channel secured the ends of the foam board and zee supports.
- A starter clip was attached to the Zee support using #12 x 1" lg. wafer-head, self-drilling screws. A minimum of two fasteners per starter clip or 12" o.c max. spacing per clip based on length of clip.
- The starter panel engaged into a starter clip and was top-fastened with #12 x 1" lg. Stainless Steel Cap head w/EPDM Sealing washer fasteners at the predrilled holes spaced at 8" o.c. max. spacing.
- The vertical edge of the panel had two (2) clips to attach that edge to the 16 ga. vertical Zee supports using (2) #12 x 1" lg. wafer-head, self-drilling screws at each clip.
- A 0.08" aluminum "J" face trim was along the bottom and sides of the mock-up that sat on top of the lower "J" trim. The face trim was secured thru the lower 16 ga. trim and into stud supports with #14 x 3" lg. wafer-head, self-drilling screw spaced at 24" o.c..
- See installation details for location of fasteners at supports and attachment of each panel.

### **Test Procedure**

The tests were conducted in accordance with the sections as shown in the following:

- ASTM E-330-02, "Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference "

## ASTM E330 UNIFORM LOAD TEST

### POSITIVE PRESSURE

Load Pressure (in-h20)	Load Pressure (psf)	Deflection #1 (in)	Deflection #2 (in)	Deflection #3 (in)
0	0.0	0.000	0.000	0.000
3	15.6	0.119	0.343	0.115
0	0.0	0.003	0.002	0.002
6	31.2	0.235	0.558	0.233
0	0.0	0.018	0.017	0.017
9	46.8	0.324	0.704	0.326
0	0.0	0.035	0.034	0.033
12	62.4	0.503	0.980	0.511
0	0.0	0.088	0.082	0.077
15	78.1	0.549	1.047	0.555
0	0.0	0.107	0.100	0.093
18	93.7	0.691	1.305	0.693
0	0.0	0.159	0.151	0.135
21	109.3	0.791	1.538	0.801
0	0.0	0.224	0.221	0.191
24	124.9	0.908	1.721	0.918
0	0.0	0.272	0.265	0.229
27	140.5	1.022	1.880	1.028
0	0.0	0.327	0.316	0.273
30	156.1	1.145	2.068	1.158
0	0.0	0.400	0.395	0.333
33	171.7	1.238	2.252	1.269
0	0.0	0.445	0.449	0.375
38.4	199.8	1.327	2.420	1.394
0	0.0	0.480	0.501	0.416

### RESULTS

Upon completion of the testing at the positive pressures noted above there were no noticeable failures of the specimen


**NEGATIVE PRESSURE**

<b>Load Pressure (in-h20)</b>	<b>Load Pressure (psf)</b>	<b>Deflection #1 (in)</b>	<b>Deflection #2 (in)</b>	<b>Deflection #3 (in)</b>
0	0.0	0.000	0.000	0.000
2	10.4	0.029	0.131	0.045
0	0.0	0.001	0.003	0.002
4	20.8	0.065	0.231	0.101
0	0.0	0.006	0.011	0.010
6	31.2	0.117	0.340	0.183
0	0.0	0.014	0.024	0.025
8	41.6	0.164	0.439	0.265
0	0.0	0.021	0.038	0.044
10	52.0	0.224	0.550	0.361
0	0.0	0.032	0.058	0.069
12	62.4	0.287	0.660	0.460
0	0.0	0.046	0.078	0.097
14	72.9	0.352	0.771	0.563
0	0.0	0.071	0.112	0.138
16	83.3	0.417	0.883	0.669
0	0.0	0.094	0.145	0.175
18	93.7	0.482	0.994	0.776
0	0.0	0.116	0.179	0.214
20	104.1	0.568	1.141	0.925
0	0.0	0.143	0.221	0.280

**RESULTS:**


Maximum Test Load = 108.3 psf (Zee support fastener pulled out of 16 ga. metal stud supports)


## STRUCTURAL TEST SETUP



X# - DEFLECTION  
LOCATION


## PLAN VIEW





Profile: ModularAL 3" PANEL


A200




8' x 8' Wall Elevation w/Metal Panels

Scale: 1 1/2" = 1'-0"









Profile: ModularAL 3" PANEL


A202



**Enlarged Detail**


**A**






Profile: ModularAL 3" PANEL


A204






Profile: ModularAL 3" PANEL



A204-1




# F-1 Enlarged Detail



# Enlarged Detail



A206



**sapa:** SAPA EXTRUSIONS, INC.  
2905 OLD OAKWOOD RD.  
GAINESVILLE, GA 30504  
770-535-1349 800-544-3801

ALUMINUM ASSOCIATION STANDARD TOLERANCES APPLY UNLESS SPECIFIED OTHERWISE		DIE NO. 052212	
UNSPECIFIED WALL THICKNESS	.093	DIFF. RATING	—
UNSPECIFIED RADIUS	.010	EST. AREA	3.34 IN <sup>2</sup>
UNSPECIFIED RATING	—	EST. WT.	.401 LBS/FT.
UNSPECIFIED RATING	—	EST. PER.	7.172 IN
UNSPECIFIED RATING	—	DUT PER.	— IN
UNSPECIFIED RATING	—	EXPD PER.	— IN
UNSPECIFIED RATING	—	FACTOR	18
UNSPECIFIED RATING	—	C.C.D.	1.755 IN


F. E. T. INC.  
Review for general compliance  
with test report AS NOTED ONLY

BY: PGF  
PROJECT # \_\_\_\_\_


PRODUCTION DRAWING
11-12-10
RELEASED DATE:
Released By: <u>Norman Liang</u>
DESTROY ALL PREVIOUS COPIES




## ADDITIONAL SUPPORT AND TRIM EXTRUSIONS




0.080" ALUM.  
STARTER CLIP



0.080" ALUM. "J" FACE TRIM  
(TESTING PURPOSES ONLY)



16 GA. ZEE SUPPORT



16 GA. "J" LOWER TRIM  
(TESTING PURPOSES ONLY)

**Spectrochemical Laboratories-Material Evaluation, Inc.**

155 Prominence Drive, New Kensington, PA, 15068

Phone: (724) 334-4140 Fax: (724) 334-4143

Date: 05-Nov-21

Page No.: 1 of 1

**Report of Tensile Testing**

Client: Farabaugh Engineering & Testing (PO #: Verbal - Pat Farabaugh)

PIN #	Dimensions (in.)		Area (sq. in.)	Yield Point (lb.)	Tensile Strength (lb.)	Yield Strength (psi.)	Tensile Strength (psi.)	Elongation (% in 2 in.)	Fracture location
	Width	Thickness							
PAC-0080"	0.4955	x 0.0770	0.0382	797	843	20900	22100	7.3	U/4 Break

Test Method: Q2300.04 rev. 14 (ASTM A370-20, E8-21, or E646-16 : Yld. by 0.2% offset, Elong. after fracture)

Equipment Used: Instron 5900R60HVL (s/n: 1602) w/ Extensometer (s/n: E93054)

Performed By: T. Ault

This test report shall not be reproduced except in full, without the written approval of the laboratory.

The recording of false, fictitious, or fraudulent statements or entries on this report may be punished as a felony under federal law.

Please send your comments and concerns to us at [feedback@spectrochemicalinc.com](mailto:feedback@spectrochemicalinc.com)

For more information call: 724-334-4140

Respectfully submitted,



Todd A. Ault

Laboratory Manager